

TSC₁₆₀



The Thermal-Eye Thermal Security Camera (TSC) is a plug-and-play, long-range security surveillance camera requiring no lighting or infrared illumination that allows for cost-efficient monitoring of large land or water areas, even in inclement weather.



The TSC delivers unmatched value and affordability for security and surveillance applications.

LONG RANGE PERIMETER SURVEILLANCE

HARBORS, WATERFRONTS AND AIRFIELDS

MEDIUM-RANGE FACILITY SURVEILLANCE

POWER PLANTS AND PUBLIC UTILITY FACILITIES

WIDE-ANGLE SECURITY SURVEILLANCE

ENTRANCES, GATES AND EQUIPMENT STORAGE

DAY AND NIGHT DETECTION OF PEOPLE,

CARS, BOATS AND MORE

BENEFITS:

- Rugged, dependable and ideal for long-range security surveillance applications
- Reduces the number of cameras required to secure a large area, decreasing overall costs and equipment required
- Designed to fit into standard enclosures and integrate with existing CCTV architecture
- Works well with intelligent software
- High performance and low maintenance with no expensive lighting or illuminators to install and maintain
- Sees easily through shadows, glare and challenging weather

FEATURES:

- Uses proven Amorphous Silicon Microbolometer detector technology
- Equipped with a serial data port for camera diagnostics
- Detects human activity at a variety of ranges: long range (2100 feet) medium range (1000 feet) or short range (300 feet)



Suspicious activity near perimeter



Airfield security breach

TSC TECHNICAL SPECIFICATIONS:

FEATURES		TSC _{SS} (Standard Series)		TSC _{XP} (Extended Performance)	
FOCAL PLANE ARRAY	MATERIAL & STRUCTURE	Amorphous Silicon Microbolometer (160 x 120 pixel array)			
	SPECTRAL RESPONSE	7-14 μm (filter bandwidth)			
	THERMAL SENSITIVITY	≤ 100 mK			
THERMAL IMAGING PERFORMANCE	START-UP TIME	~ 7 sec			
	CONTRAST/BRIGHTNESS	Enhanced Image Processing			
OPTICS	FOV ALTERNATIVES	Wide-Angle (50° x 35°)	Med.-Range (17° x 12°)	Wide-Angle (50° x 35°)	Med.-Range (17° x 12°)
	RANGE TO DETECT HUMAN ACTIVITY	Up to 300ft (90m)	Up to 1000ft (300m)	Up to 300ft (90m)	Up to 1000ft (300m)
	FOCUS	Fixed	Manual adjust	Fixed	Manual adjust with passive athermalized lens
VIDEO	FORMAT	Analog: SMPTE-170 (cf. NTSC Compatible, monochrome)			
	SYNCHRONIZATION	Line Sync when 24 VAC power used			
POWER	INPUT VOLTAGE	24 VAC or 9-30 VDC (Note: full function rear cover option required for 9-30 VDC.)			
	INPUT POWER	< 2.0 W for 9-30 VDC Input and < 3 W for AC input at all temperatures			
ENVIRONMENTAL CHARACTERISTICS	OPERATING TEMPERATURE (AMBIENT AIR TEMPERATURE)	For indoor use without an enclosure: 6°C TO 40°C (42.8°F TO 104°F) For outdoor use with a protective enclosure: -14°C TO 40°C (6.8°F TO 104°F) (notes 1 and 2)		For indoor or outdoor use: -20° C TO 60°C (-4°F TO 140°F) (see notes 2 and 3 below)	
	STORAGE TEMPERATURE	-40°C TO 85°C (-40°F TO 185°F)		-40°C TO 85°C (-40°F TO 185°F)	
	EMC COMPLIANCE	FCC Part 15 & CE Mark		FCC Part 15 & CE Mark	
PHYSICAL CHARACTERISTICS	SIZE	7.7"L X 1.9"W X 2.3"H (3.8CM X 0.75CM X 0.91CM)		8.0"L X 1.9"W X 2.3"H (3.1CM X 0.75 CM X 0.91CM)	
	COLOR	Silver Extruded Anodized Aluminum		Black Extruded Anodized Aluminum	
	WEIGHT	14 OZ (460G)		16 OZ (525G)	
	MOUNTING BRACKET	1/4" - 20 UNC-2B Universal top or bottom mount		1/4" - 20 UNC-2B Universal top or bottom mount	
ORDERING INFORMATION	FOV ALTERNATIVES	Wide FOV (50° X 35°)	Medium FOV (17° X 12°)	Wide FOV (50° X 35°)	Medium FOV (17° X 12°)
	24 VAC REAR COVER, NTSC LINE LOCK (NOTE 3)	4978510-0002	4978510-0001	N/A	N/A
	FULL FUNCTION REAR COVER, NTSC LINE LOCK (NOTE 4)	N/A	N/A	4978520-0004	4978520-0003
ADDITIONAL CAMERA	FULL FUNCTION REAR COVER (REQUIRED)	Choice of power input: 24 VAC or 9-30 VDC			
OPTIONAL ENCLOSURE WINDOW KITS - PART NUMBERS	FOR PELCO 2500 SERIES	4" dia. window frame 4978525-1* or -2**			
	FOR PELCO 3500 SERIES	2.9" x 2.5" dia. window frame 4978535 -1* or -2**			
	FOR PELCO 4700 SERIES	4.3" x 3.9" dia. window frame 4978547 -1* or -2**			
	FOR PHILIPS 948X SERIES	2.75" dia. window frame 1669398 -1* or -2**			
	FOR UNIVERSAL SERIES (NOTE 5)	6" x 6" dia. window frame 4978540 -1* or -2**			
		-1* Germanium window (96% Trans in 7-14 μm) 2.25" Diameter			
	-2** Silicon window (73% Trans in 7-14 μm) 2.25" Diameter				

Specifications subject to change without notice

TSC 160 RevA January 2008

This technical data and software is considered as Technology Software Publicly Available (TSPA) as defined in Export Administration Regulations (EAR) Part 734.7-11.

Notes:

- For outdoor use, the TSC_{SS} is assumed to be installed in a PELCO enclosure, model EH4718-2, with heater, defroster, blower, and sun shroud options, and with the vent covers installed, or equivalent NEMA 4 rated enclosure.
- When used in an enclosure, an infrared-transmitting window must be installed. Infrared window conversion kits are available for the following PELCO enclosure products: PELCO Series 2500 enclosure, PELCO Series 3500 enclosures, PELCO Series 4700 enclosures.
- For outdoor use, a UL-approved protective enclosure with NEMA 4 rating must be used.
- Other video formats also available.
- Universal Series Enclosure window comes as a kit designed to fit the intended enclosure after being sized by the installer. The silicon or germanium window is then bonded into the frame using the provided bonding material and instructions, to ensure proper fit and function.

L-3 Communications Infrared Products 13532 North Central Expwy., MS 37 Dallas, Texas 75243

800-990-3275 972-528-1300 www.L-3com.com/IRP www.Thermal-Eye.com

