



Annular mini ringlight 18,5 mm

Mini Ringlights

Features:

- Continuous ring of illumination fiber within the housing.
- Mounts directly to objective by means of thumb screw.
- Optimized illumination of the mini ringlights only requires a comparably small fiber bundle diameter. This can be well illuminated by KL 200, KL 1500 LCD as well as KL 2500 LCD.
- Therefore SCHOTT Mini Ringlights have an interchangeable adapter with removable ferrules, which allows the connection to all three light sources.
- Manufactured in the EU.

Benefits:

- Absolute shadow-free illumination.
- Small dimensions for easy handling.

Mini Ringlights									
Cold light source	Part-No.	Type	Length	Inner Ø	Outer Ø	Height	Working distance	Active Ø/ branch	Outer Ø jacketing
			L	ID	OD	H	A	b	D
KL 200	157 018	Slit-RL 18.5 mm Ø	1000 mm	18.5 mm	34 mm	18 mm	20–70 mm	4 mm	7.6 mm
			39.37 inch	0.73 inch	1.34 inch	0.71 inch	0.79–2.76 inch	0.16 inch	0.30 inch
KL 1500 LCD	157 025	Slit-RL 22/25 mm Ø	1000 mm	22/25 mm	40 mm	20 mm	20–70 mm	5 mm	8.8 mm
			39.37 inch	0.87/0.98 inch	1.58 inch	0.79 inch	0.79–2.76 inch	0.20 inch	0.35 inch
KL 2500 LCD	157 030	Slit-RL 30 mm Ø	1000 mm	30 mm	52 mm	22 mm	20–70 mm	5 mm	10.8 mm
			39.37 inch	1.18 inch	2.05 inch	0.87 inch	0.79–2.76 inch	0.20 inch	0.43 inch
	157 040	Slit-RL 40 mm Ø	1000 mm	40 mm	64 mm	24 mm	20–70 mm	7 mm	11.8 mm
			39.37 inch	1.58 inch	2.52 inch	0.95 inch	0.79–2.76 inch	0.28 inch	0.47 inch

Mini Ringlights

