



6-point ringlight 58 mm

6-Point Ringlights

Feature:

- Six illumination spots designed within housing.
- Mounts directly to objective by means of thumb screw.
- Housing made of rugged, black anodized aluminium.
- Fiber bundle protected with flexible metal PVC sheathing.
- Manufactured in the EU.

Benefit:

- Cost effective in comparison to annular ringlights
- Illumination with reduced shadows, but still sufficient shadows for improved contrasts.

| 6-Point Ringlights | | | | | | | | | | |
|--------------------|----------|---------|-----------------------|--------------------|--------------------|--------------------|----------------------------|---------------------|----------------------|---------------------------|
| Cold light source | Part-No. | Type | Length | Inner Ø | Outer Ø | Height | Working distance | Active Ø/ branch | Outer Ø Jacketing | Light source adapter Ø |
| | | | L | ID | OD | H | A | b | D | F |
| KL 200 | 172 501 | 58 mm Ø | 1000 mm 39.37 inch | 58 mm 2.28 inch | 86 mm 3.39 inch | 23 mm 0.91 inch | 40–80 mm 1.58–3.15 inch | 6 mm 0.24 inch | 10.8 mm 0.43 inch | 9 mm 0.35 inch |
| | 172 601 | 66 mm Ø | 1000 mm 39.37 inch | 66 mm 2.60 inch | 94 mm 3.70 inch | 23 mm 0.91 inch | 40–80 mm 1.58–3.15 inch | 6 mm 0.24 inch | 10.8 mm 0.43 inch | 9 mm 0.35 inch |

6-Point Ringlights

