

## 2.4GHz Receivers

### Features

#### 2.4 GHz AV Wireless Receivers

- 4 or 8 AV receiver device
- Auto or Manual switching
- Compact size



BRX-2408



BRX-2404



BRX-2404E

### Specification

	BRX-2408	BRX-2404	BRX-2404E
Frequency	8 Channel 2.413 MHz ~ 2.510 MHz	4 Channel 2.413 MHz ~ 2.470 MHz	4 Channel 2.413 MHz ~ 2.470 MHz
Power Consumption	12V DC, 240mA	12V DC, 280mA	12V DC, 500mA
Video Output	NTSC, 75 Ohm 1 Vp-p		
Audio Output	10k Ohm		
Sub Carrier Freq.	6.5MHz	5.5MHz	
Operating Temperature	-10 ~ 40 °C		
Storage Temperature	-40 ~ 80 °C		
Operating Humidity	20 - 80%		
Storage Humidity	10 - 80%		
Dimension & Weight	Excluding SMA Connector 80 x 63 x 20 mm 95g	Excluding SMA Connector 115 x 80 x 20 mm 150g	80 x 80 x 35 mm 220g



**BOCK OPTRONICS INC.**  
14 Steinway Blvd., Unit 7  
Toronto, Ontario M9W 6M6, Canada  
Tel: 416-674-2804 Fax: (416) 674-1827

Quebec & Eastern Canada  
Tel: 450-662-9889  
Fax: 450-662-9063

Website: [www.bockoptronics.ca](http://www.bockoptronics.ca)  
E-mail: [sales@bockoptronics.ca](mailto:sales@bockoptronics.ca)