

2.4GHz Transmitter Modules

Features

- 2.4 GHz band frequency transmission
- Compact size units
- 4 Channel DIP switch selectable
- Using digital phase-lock-loop circuit w/o temperature drifting problem



Specification

	BTX-24100M	BTX-24010M
Transmission	4 Channel	
Frequency	2.413 MHz ~ 2.470 MHz	
Transmission Power	1W	100mW
Nominal Output Impedance	50 Ohm	
Operating Voltage	12V DC, 500mA	12V DC, 150mA
Video Input	75 Ohm, 1 Vp-p	
Audio Input	10k Ohm, 1 Vp-p	
Sub Carrier Freq.	6.5Mhz	
Operating Temp.	-10 ~ 40 °C	
Storage Temp.	-40 ~ 80 °C	
Operating Humidity	20 - 80%	
Storage Humidity	10 - 80%	
Dimension & Weight	Excluding SMA Connector 118 x 60 x 35 mm 320 g	



BOCK OPTRONICS INC.
 14 Steinway Blvd., Unit 7
 Toronto, Ontario M9W 6M6, Canada
 Tel: 416-674-2804 Fax: (416) 674-1827

Quebec & Eastern Canada
 Tel: 450-662-9889
 Fax: 450-662-9063

Website: www.bockoptronics.ca
 E-mail: sales@bockoptronics.ca