

SOLO - ACCESSORIES

SOLO Handheld Controller

The **domo** Handheld Controller is a dedicated set-up device which provides clients with the ability to configure SOLO transmitters and receivers without the presence of a laptop and control application. The compact controller operates with a touch screen and daylight-viewable LCD and is housed in a rugged aluminium enclosure. As it is a low power device, it can be run on rechargeable batteries, adding to the portability. However, the system can also be run from an external power supply. The controller has been designed to operate on a "plug and play" basis and can detect multiple connected devices, like the receivers in the **domo** MultiPIX.

Features:

- Compact and portable
- Can connect to any SOLO transmitter/receiver
- Low power consumption
- Rechargeable batteries or 12V DC input
- Robust aluminium enclosure
- Daylight-viewable LCD with touch screen
- Sleep mode to aid battery life
- Receiver status page to free up front panel for video only.



Specification:

Input	
12V DC in	Lemo
Battery charger	Mini DC power socket
Input/Output	
RS-232 Control	Lemo
RS-232 Data	Lemo
Physical	
Dimension Base Unit	L 266mm, W 168mm, H 32mm
Weight Base Unit	1kg
Power	
DC input	6 to 12V
Internal NiMH rechargeable batteries	6 x 1.2V = 7.2V
Power Consumption (operating)	≤1.5W
Power consumption (asleep)	<25 mW
Environment	
Temperature Range	-10 to +50 deg C

Products are available to security users only, in licensed frequency bands. These products are not approved for use by unlicensed users. Commercial products are available to unlicensed users - contact **domo** direct for details.

Product Code: SOLCON

SOLO - ACCESSORIES

Battery Pack for SOL4TX



Rechargeable battery pack, including interconnecting power cable, for use in conjunction with SOLO Transmitter.

Product Code: BAT4AH

SOL4TX Harness Kit



Slim fit overt body harness suitable for use with SOLO or SOLO Transmitter.

Product Code: ACCBCH

TX Antenna L or S Band and Cable



Small compact directional antenna, specifically designed for use with SOLO Transmitter, including short interconnecting cable terminated to suit TX.

Product Code: ANTBCL ANTBCS


TX-RX Antenna L or S Band



Co-linear omni-directional antenna 4.5dbi. Suitable for use with either transmitter or receiver. TNC base mounted connection.

Product Code: ANT4L ANT4S

TX-RX Antenna L or S Band



Directional antenna 12dbi. Suitable for use with either transmitter or receiver. TNC base mounted connection.

Product Code: ANT12L ANT12S

Power Supply



AC input 100-240V. DC output 12V 3.0 Amp. Standard cable and connector. For use with SOLO2 or SOLO4 TX or RX unit.

Product Code: PSU12

Cables



A variety of standard cables are available for most applications.

Please contact **domo** or your supplier for product code

Products are available to security users only, in licensed frequency bands. These products are not approved for use by unlicensed users. Commercial products are available to unlicensed users - contact **domo** direct for details.



domo

domo is at the forefront of innovation, developing technologies in the fields of digital wireless, video, audio, telemetry and IP.

Our key technology expertise is in digital video processing, digital modulation and Internet Protocol (IP) interfacing.

Our strength is in adapting complex technologies into simple-to-operate, robust solutions.

Our team of dedicated **domo** engineers is continually developing new solutions directed by demanding customer requirements in fields such as:

- Police Forces
- Security Services
- Special Forces
- Homeland Security Agencies
- First Responders
- Fire Services
- Port Security
- Traffic Management Agencies.