SnakeEye™

SnakeEye[™] is a low-cost hand held remote video inspection system. Lightweight, modular and portable, SnakeEye[™] "lets your eyes travel where you can't." Combining a CCD camera and TFT-LCD display technology, SnakeEye[™] delivers crystal-clear, full color video at a fraction of the price of current remote video inspection systems.

SnakeEye[™] is modular in design so that it can be easily configured to inspect ... behind walls, inside ceilings, in and around pipes and machinery, under vehicles and aircraft, inside engine compartments, behind computer equipment, underneath automobile dashboards ... the possible uses are endless. SnakeEye[™] is ideal for quick, non-destructive, qualitative inspections in hard-to-reach places.

SnakeEye[™] achieves its versatility with an interchangeable camera head that can be attached to a rigid wand, a ring finger attachment or extendible cables. SnakeEye[™] comes equipped with a full range of accessories and also has plug-in capabilities, one of which allows the user to connect to a standard VCR to record and playback images.

SnakeEye[™] is designed to function in harsh industrial and commercial environments and is constructed of high impact, heavy duty plastic that can withstand shock and vibration. SnakeEye[™] resists water, dust, and dirt particles and can also be used where grease and non-solvent based chemicals are present.



A	Specification	
ring adapter	Display Unit	 5 in (12.7 cm) color TFT-LCD 320 x 234 color pixels Rotatable Anti-glare screen Adjustable hand strap Backlight brightness adjustment High/Low Camera probe light control On/Off External power port Video I/O port Water resistant
	Camera	 CCD camera 1.2 in (3.0 cm) diameter Removable Sensitivity 10 lux Resolution 512 x 492 Field of view 46 degrees 4 White light LEDs Water proof to 100 ft (30m)
extension cable adapters	Power System	 Up to 90 min continuous operation 2 x 6 V NiMH rechargeable batteries Battery fast charger AC/DC adapter 12 V auto adapter
wand adapter	Camera Adapters	 18 in (45.7 cm) length 90 degree one way articulation Sure-grip handle
	C-Mount Camera	Adapts SnakeEye to fiberscopes and borescopes
•	Attachments	• 4 ft (1.2 m) flexible cable • Carrying case • Video I/O cable
carrying case	General	 Total system weight- less than 2.5 lbs (1.1 kg) Power requirements: AC Nominal input: 100-240 V, DC nominal input: 12V System operating temperature- 32 degrees F to 122 degrees F (O degrees C to 50 degrees C) Video input/output- NTSC

10.00



removable camera head

power system

rigid

BOCK OPTRONICS INC. 14 Steinway Blvd., Unit 7 Toronto, Ontario M9W 6M6, Canada Tel: 416-674-2804 Fax: (416) 674-1827 Quebec & Eastern Canada Tel: 450-662-9889 Fax: 450-662-9063 Website: www.bockoptronics.ca E-mail: sales@bockoptronics.ca